



## Ceiling-Light SERIES

### SPECIFICATIONS

#### LED

SMD



CCT



#### Finish



#### Material Description

Housing: Die-cast aluminum  
Diffuser: Optical PMMA Lens


#### Beam Angle



#### Dimming Options



#### Photometric



For detailed technical project cut sheet can be requested by our online portal at [www.priorled.com](http://www.priorled.com)

#### FAMILY RANGE

| Code        | Power | Dimensions | Cut-Out  |
|-------------|-------|------------|-------------------------------------------------------------------------------------------|
| M-CL-104436 | 36W   | Ø300*H58mm | -                                                                                         |
| M-CL-104448 | 48W   | Ø400*H58mm | -                                                                                         |
| M-CL-104496 | 96W   | Ø600*H58mm | -                                                                                         |

#### PARAMETERS

|                   |                    |
|-------------------|--------------------|
| Efficacy          | 120lm/W            |
| CRI               | >90                |
| Adjustable        | NO                 |
| Color Consistency | SDCM               |
| Pf                | 0.9                |
| Input Voltage     | AC100-240V 50/60Hz |
| Operating Temp.   | -20°C~60°C         |
| Working Hours     | 50,000 Hrs         |

#### APPLICATION

- Modern Work spaces
- Institutions
- Retail Outlets
- Hotels
- High end Villa's

#### DRAWING Unit:mm

