




## TD SERIES

### SPECIFICATIONS

#### FAMILY RANGE

Code	Power	Dimensions	Cut-out 
TD-1037-07	07W	Φ68*54mm	Φ60mm
TD-1037-09	09W	Φ68*54mm	Φ60mm
TD-1037-13	13W	Φ68*54mm	Φ60mm

#### PARAMETERS

Efficacy	100lm/W
CRI	>90
Adjustable	NO
Color Consistency	SDCM
Pf	0.9
Input Voltage	AC220-240V 50/60Hz
Operating Temp.	-20°C~60°C
Working Hours	50,000 Hrs

#### APPLICATION

##### 1. Residential Applications:

- Living Rooms
- Bedrooms
- Kitchens
- Bathrooms
- Hallways

##### 2. Commercial Applications:

- Offices
- Retail Spaces
- Restaurants and Bars
- Hotels and Hospitality
- Showrooms

#### DRAWING Unit:mm



#### LED

COB



CCT

- 2700K
- 3000K
- 4000K


#### Finish



#### Material Description

Housing: Die-cast aluminum  
Reflector: Prismatic aluminum  
Diffuser: Tempered clear glass


#### Beam Angle



#### Dimming Options



#### Photometric



For detailed technical project cut sheet can be requested by our online portal at [www.priorled.com](http://www.priorled.com)

