



TD SERIES

SPECIFICATIONS

FAMILY RANGE

Code	Power	Dimensions	Cut-out 
TD-1035-09	09W	Φ80*H48mm	Φ75mm
TD-1035-15	15W	Φ115*60mm	Φ100mm
TD-1035-20	20W	Φ160*75mm	Φ140mm
TD-1035-30	30W	Φ160*75mm	Φ140mm
TD-1035-40	40W	Φ215*98mm	Φ200mm

PARAMETERS

Efficacy	100lm/W
CRI	>90
Adjustable	NO
Color Consistency	SDCM<3
Pf	0.9
Input Voltage	AC220-240V 50/60Hz
Operating Temp.	-20°C~60°C
Working Hours	50,000 Hrs

APPLICATION


1. Residential Applications:

- Living Rooms
- Bedrooms
- Kitchens
- Bathrooms
- Hallways

2. Commercial Applications:

- Offices
- Retail Spaces
- Restaurants and Bars
- Hotels and Hospitality
- Showrooms

DRAWING Unit:mm



LED

COB



CCT

- 2700K
- 3000K
- 4000K


Finish



Material Description

Housing: Die-cast aluminum
Reflector: Mirror finished aluminum
Diffuser: PMMA Opal pc Lens


Beam Angle



Dimming Options



Photometric



For detailed technical project cut sheet can be requested by our online portal at www.priorled.com

