

# PRIOR



## TD SERIES

### SPECIFICATIONS

#### LED

| COB                                                                                 | CCT                                                |
|-------------------------------------------------------------------------------------|----------------------------------------------------|
|  | <div>3000K</div> <div>4000K</div> <div>6000K</div> |


#### Finish



#### Material Description

Housing: Die-cast aluminum  
Reflector: Prismatic aluminum  
Diffuser: Tempered Clear Glass


#### Beam Angle



#### Dimming Options



#### Photometric



For detailed technical project cut sheet can be requested by our online portal at [www.priorled.com](http://www.priorled.com)

#### FAMILY RANGE

| Code       | Power | Dimensions | Cut-out  |
|------------|-------|------------|-------------------------------------------------------------------------------------------|
| TD-1044-08 | 08W   | 80*80*70mm | 70*70mm                                                                                   |
| TD-1044-10 | 10W   | 80*80*70mm | 70*70mm                                                                                   |
| TD-1044-13 | 13W   | 80*80*70mm | 70*70mm                                                                                   |

#### PARAMETERS

|                   |                    |
|-------------------|--------------------|
| Efficacy          | 100lm/W            |
| CRI               | >90                |
| Adjustable        | YES                |
| Color Consistency | SDCM               |
| Pf                | 0.9                |
| Input Voltage     | AC100-240V 50/60Hz |
| Operating Temp.   | -20°C~60°C         |
| Working Hours     | 50,000 Hrs         |

#### APPLICATION

##### 1. Residential Applications:

- Living Rooms
- Bedrooms
- Kitchens
- Bathrooms
- Hallways

##### 2. Commercial Applications:

- Offices
- Retail Spaces
- Restaurants and Bars
- Hotels and Hospitality
- Showrooms

