



TD SERIES

SPECIFICATIONS

FAMILY RANGE

Code	Power	Dimensions	Cut-out 
TD-1044-08	08W	80*80*70mm	70*70mm
TD-1044-10	10W	80*80*70mm	70*70mm
TD-1044-13	13W	80*80*70mm	70*70mm
TD-1044-15	15W	110*110*80mm	100*100mm

PARAMETERS

Efficacy	100lm/W
CRI	>90
Adjustable	YES
Color Consistency	SDCM<2,3
Pf	0.9
Input Voltage	AC100-240V 50/60Hz
Operating Temp.	-20°C~60°C
Working Hours	50,000 Hrs

APPLICATION


1. Residential Applications:

- Living Rooms
- Bedrooms
- Kitchens
- Bathrooms
- Hallways

2. Commercial Applications:

- Offices
- Retail Spaces
- Restaurants and Bars
- Hotels and Hospitality
- Showrooms

DRAWING Unit:mm



LED

COB



CCT

- 3000K
- 4000K
- 6000K


Finish



Material Description

Housing: Die-cast aluminum
Reflector: Prismatic aluminum
Diffuser: Tempered Clear Glass


Beam Angle



Dimming Options



Photometric



For detailed technical project cut sheet can be requested by our online portal at www.priorled.com

